

Caster-Steer Trailers

Capacity Range
2,000 – 4,000 lbs.



CA1300
Capacity 3000-4000 lbs.
Steel frame, hardwood deck.
Heavy duty couplers.



CA1310
Capacity 3000-4000 lbs.
All steel construction.
Heavy duty couplers.



CA1108
Capacity 2000 lbs.
Steel frame, hardwood deck.
Some models PRONTO®.

QUALITY FEATURES

- Standard deck sizes: widths 30", 36", 42" or 48"; lengths 60", 72", 84", or 96". Special sizes available to suit.
- Standard running gears: **2,000 lbs. capacity** –Moldon Rubber wheels 12" x 3" on 1" dia. axle, swivel caster wheels 8" x 2", platform height 14". **3,000 lbs. capacity**–Moldon Rubber wheels 12" x 3" on a 1¼" dia. axle, swivel caster wheels 8" x 3", platform height 15¾". **4,000 lbs. capacity**–Moldon Rubber wheels 12" x 3½" on a 1¼" dia. axle, swivel caster wheels 10" x 3", platform height 15¾".
- Swivel casters drop-forged steel (80,000 psi tensile strength) with integrally forged kingpin, precision tapered thrust bearing and hardened ball raceways, unless otherwise specified.
- Casters bolted to structural steel cross bolsters.
- All corners mitered.
- Standard with one pipe rack 26" high above deck, and channel-reinforced external pipe sockets at swivel caster end. Additional rack(s), side sockets on request.
- Precision Ball or Tapered bearings in all wheels.
- Hardwood decks sanded and varnished; steelwork enameled Hammertone Blue (or Safety Orange if specified).

UNIQUE SPECIFICATIONS

CA1300 Wood deck: 1" select hardwood set flush in 3" x 2" x ¼" steel angle frame with two 2" x 2" x ¼" center longitudinals.

CA1310 All steel: 12 ga. deck welded to 3" channel frame and center longitudinal.

CA1320 Wood deck: 1" select hardwood set flush in 2" x 2" x ⅜" steel angle frame with full length 1" x 1" x ⅜" center angle.

CA1330 All steel: 12 ga. deck welded to 2" channel frame and center longitudinal.

Models CA1320 and CA1330 are designed for up to 2,000 lbs. capacity.

CA1108 Wood deck: 1" select hardwood set flush in 2" x 1½" x ⅜" steel angle frame. All wheels 8" x 2" with precision ball bearings.

Series WH casters bolted to ⅜" steel angle cross bolsters. Removable pipe handle in sockets with set screws. All wheels 8" x 2". Platform height 11¾".

To order, specify model number and suffix
CA1108 Trailer Selection Table

Platform Size Inches	SELECTION SUFFIX				Approx. Weight Lbs.
	Duralast®	Polysoft®	Polylast Donut	Moldon Rubber †	
24 x 48	-8DB2448	-8SPB2448	-82AYB2448	-8RB2448	205
30 x 48	-8DB3048	-8SPB3048	-82AYB3048	-8RB3048	215
30 x 60	-8DB3060	-8SPB3060	-82AYB3060	-8RB3060	230
36 x 60	-8DB3660	-8SPB3660	-82AYB3660	-8RB3660	250
36 x 72	-8DB3672	-8SPB3672	-82AYB3672	-8RB3672	270

† Moldon Rubber wheels limit capacity to 1,600 lbs. with 6" wheels.