

### Drum Handling Equipment Capacity Range up to 1,000 lbs.



Use rear wheels to tip nose of Model 59 up onto pallet.



★All models on this page are shippable **PRONTO®**.

### Drum-and-Barrel Movers

Choose popular Model HM49, self-standing Model HM60, or pallet-loading Model HM59 to handle your drums or barrels. All three have a sliding "triple duty" chime hook that fits most metal drums, wood barrels, or open fiber drums.

Heavy duty roller bearings and lube fittings in all wheels: choice of 10" x 2½" Moldon Rubber or Plastex, or 10" x 3.40-5 Pneumatic tires (not available on Model HM59). Model HM59 has two 6" x 2" auxiliary wheels on a ¾" rear axle, plus "handle bar" for tilting truck back, designed for pallet-loading or simply to ease operator strain.



1. Lean truck against drum and drop hook over rim.

2. Step on foot bar and pull back on handles.

### QUALITY FEATURES

- Handle length . . . . .62"
- Overall width . . . . .23"
- Axle diameter . . . . .1"
- Capacity . . . . .1,000 lbs.
- Weight **No. HM49** . . . . .75 lbs.
- No. HM59** . . . . .97 lbs.
- No. HM60** . . . . .82 lbs.

TO ORDER, SPECIFY MODEL NUMBER AND SUFFIX

SELECTION SUFFIX		
Moldon Rubber	Plastex	Pneumatic Tires (N.A. #59)
-R	-P	-PR

### Drum Cradles

This sturdy, all-welded steel drum cradle comes ready to use—no assembly. Features two 2½" swivel casters at one end and two 3" sintered iron wheels at the other. Wheels are plain bore. Model DR545 comes with sliding hook; if no handle desired specify DR545-L. Also available without wheels (DR546), or without wheels or handle (DR546-L). Height 19" (incl. wheels), width 17"; length 31" (excl. handle). Capacity 800 lbs. Weight 32 lbs.

★Shippable **PRONTO®** via UPS.

### ★DR545 & ★DR546



For proper use, simply: 1) lean cradle against drum with nose prongs astride bottom chime; 2) pull out handle and position hook over chime of drum; 3) pull back on handle and drum will seat onto prongs for tipping into horizontal position.