

Extra-thick, extra-wide rubber or urethane tread wheels are available in a variety of popular sizes for use on industrial trailers and wagons in the 5-ton class and up. The solid tires are chemically bonded to replaceable steel rims, which are “pressed on” to a heavy-duty cast iron center. Both rubber and polyurethane wheels feature a smooth tread design and sealed tapered roller bearings are standard.

Sizes are expressed as 15" x 7" x 11¼", where the first number expresses the tire diameter, the second number the rim width, and the third number the inside diameter of the steel rim.

*Additional non-stock sizes are available, consult factory.*

### OPTIONAL EXTRAS

- Special Compounds – Neoprene, non-marking and 90-durometer “extra hard” rubber tires available.
- Special Treads – Non-Skid tread (slots in tread as shown below) is available on rubber-tired wheels. Most polyurethane tires are available with a grooved tread.




*To order, add bearing size to catalog number.  
Example: W-POR-1890-2  
(For polyurethane tread change “POR” to “POY”)*

Dimensions in Inches

Dia.	Face	Rim	Capacity (6 mph)		Capacity (10 mph)		Tapered Roller Bearings			Wt. Lbs.
			Rubber	Poly	Rubber	Poly	Hub Length	Catalog Number	Bearing Sizes	
15	5	11¼	2850	4380	2540	3880	5½	W-POR-1550-	1¼-1½	103
	6		3530	5440	3150	4800	6½	W-POR-1560-	1¼-1½	108
	7		4210	6480	3770	5730	6½	W-POR-1570-	1¼-1½	114
	8		4890	7530	4380	6650	8½	W-POR-1580-	1¾-2	198
	9		5370	8700	4750	7700	8½	W-POR-1590-	1¾-2	200
16¼	5	11¼	3120	4800	2760	4250	5½	W-POR-1650-	1¼-1½	107
	6		3900	6050	3470	5360	6½	W-POR-1660-	1¼-1½	114
	7		4740	7300	4190	6450	6½	W-POR-1670-	1¼-1½	122
18	5	12½	3360	5770	2980	4590	5½	W-POR-1850-	1¼-1½	145
	6		4290	6610	3800	5850	6½	W-POR-1860-	1¼-1½	153
	7		5220	8040	4620	7110	6½	W-POR-1870-	1¼-1½	162
	8		6150	9470	5450	8380	8½	W-POR-1880-	1¾-2	225
	9		7080	10900	6280	9660	8½	W-POR-1890-	1¾-2	234
20	5	16¼	3100	5480	2750	4850	5½	W-POR-2050-	1¾-2	211
	6		4440	6840	3920	6040	6½	W-POR-2060-	1¾-2	217
	7		5290	8160	4680	7210	6½	W-POR-2070-	1¾-2	225
	8		6170	9500	5440	8410	8½	W-POR-2080-	1¾-2	328
	9		6575	10800	5820	9560	9½	W-POR-2090-	1¾-2	335
22	7	16¼	6080	9360	5380	8290	6½	W-POR-2270-	1¾-2	239
	8		7170	11040	6340	9760	8½	W-POR-2280-	1¾-2	342
	10		9325	14400	8260	12740	9½	W-POR-2210-	1¾-2	367

Tire Only Catalog Number	Wt. Lbs.
T-1550-POR	27
T-1560-POR	32
T-1570-POR	38
T-1580-POR	45
T-1590-POR	47
T-1650-POR	31
T-1660-POR	38
T-1670-POR	46
T-1850-POR	37
T-1860-POR	45
T-1870-POR	54
T-1880-POR	60
T-1890-POR	69
T-2050-POR	41
T-2060-POR	47
T-2070-POR	55
T-2080-POR	63
T-2090-POR	70
T-2270-POR	69
T-2280-POR	77
T-2210-POR	102



Sealed bearing configuration

♣ Does not include spacers/thrust washers which add approximately ¼" to hub length.  
♣ Catalog number shown is for rubber tread; to order polyurethane change "POR" to "POY".