



Heavy-Duty Contact Brake.† Newly available on the Maxi-Duty and Dual Wheel Maxi-Duty Casters, this brake is activated by tightening the brake-shoe against the wheel(s). The “thumbscrew” design provides adjustable brake pressure. Add suffix **-HCB** on Series MD, **-DHCB** on Series MDD.



Dual Tread Contact Brake.† This brake (suffix **-DCB**) is designed for Series 7200 pneumatic casters. A pull on the lever at the back of the caster forces a non-skid pad against both wheels. Constructed of heavy duty steel components, this brake features an adjusting rod to compensate for tread wear and inflation pressure.



Foot-Activated Contact Brake.† This unique brake (suffix **-FCB**) is available on Series A, CH, EHD and 7000 Pneumatic tired (up to 16" models) casters. Pushing down on the T-handle clamps a non-skid pad against the wheel. Easily operated by foot, the brake disengages by flipping the handle in the opposite direction. The brake is constructed of all-steel components and is adjustable.



InstOEmatic Wheel Brake (U.S. Pat. No. 3467981). This static foot-operated brake is available on series A, CH, EHD, ES, FM, HS, WH, and various 7000 and 8000 series models (NA with wheels having tapered or ball bearings). Stepping down on either end of the pedal forces three steel plungers against a washer which contacts the wheel hub. To order, add suffix **-IB** for *Rap-A-Round* version, suffix **-IRB**.



Tread Contact Brake.† Stepping down on the lever forces a non-skid pad against the wheel tread. This brake is offered on Series 52 casters, Thread Guard casters (TG and TX) and various 4000 and 8000 series casters (suffix **-CB**). Available with all-stainless steel components for stainless steel casters (on Series STA, suffix **-SCB**; on Series STL, suffix **-SLCB**).



Side Foot Brake. This husky all-steel wheel brake (suffix **-FB**) is available on Whirlaway (WW), Medium Service (MS), General Service (GS), Series 52, and various 8000 series models. The oversize foot pedal utilizes cam action to lock the wheel, but the unique design permits a full length spanner bushing to maintain caster strength. For *Rap-A-Round* pedal extension, allowing all-around accessibility, add suffix **-FRB**.



Thumbscrew Wheel Brake. An effective yet simple brake. Turning the screw forces the thrust washer against the wheel hub, resulting in positive locking of the wheel. Available on most swivel or rigid Hamilton casters. To order, add suffix **-B** (**-HB** for Maxi-Duty casters) to catalog number of desired caster.



Toe Brake. This economical brake activates by pushing down the “toe-size” pedal which pinches the wheel between the caster legs. Available with Series HL and 300 swivel casters models (add suffix **-TB**).



Combination Brake. Available on most Series 300 swivel models, the combination brake (suffix **-LCB**) is activated by stepping down on the pedal locking both the swivel mechanism and the wheel simultaneously. (For a complete series of heavier plate-type combination brake casters with 2" face wheels, see pg. 41.)



Optional *Rap-A-Round* pedal extension provides convenient all-around accessibility. Available on InstOEmatic Brake (suffix **-IRB**) and Side Foot Brake (suffix **-FRB**).

† These brakes are most effective on resilient tread wheels, e.g. polyurethane or rubber.

NOTE: Brakes are not designed to stop moving equipment nor are they intended for use on ramps or inclines.

★ = available **PRONTO**®!

Series Abbv.	Page Ref.	BRAKE OFFERINGS (SUFFIX)
MD	17	-HCB, -HB
MDD	18	-DHCB
PSD	19	-B
EHD	20-21	-FCB, ★-IB, -IRB, -B
CH	22	-FCB, ★-IB, -IRB, -B
A	23	-FCB (except 5" & 6" swivels), ★-IB, -IRB, -B
ES	24	★-IB, -IRB, -B
FM	25	★-IB, -IRB, -B
HS	26	★-IB, -IRB (except 3¼" models), -B
WH	27	★-IB, -IRB, -B
MS	28	-FB, -FRB, -B
GS	29	-FB, -FRB (except 3¼" models), -B
52	30-31	(-CB, ★-FB, -FRB -these three brakes 4" & larger only), -B
WW	32	-FB (except 8"), -FRB (except 3¼" & 8" models), -B
HL	335	★-B (3" swivels only), ★-TB (swivels, except 3" models)
200	34	-B
300	35	-TB (plate-type swivels only), -LCB (plate-type swivels, except 3" models), -B (rigids only)
7000	38	-FCB (8" thru 18" models), -IB/-IRB (8" thru 12" models), -B (8" thru 12" models), -HB (16" & 18" models)
7200	39	-DCB
5000	40	-IB (8" & 10" only)
8000	42	★-IB/-IRB (#8008/8010/8410/8412), -CB (#8526/8528), -FB/-FRB (#8006/8208/8526/8528), -B
4000	43	-CB (#4208)
STA	44	-SCB (swivels only)
STL	45	-SLCB (swivels, except 3½" models)
TG	46	-CB
TX	47	-CB
V	48	See respective caster series.