

## Wash Down

**Load Rating (ea.): 240 – 1600 lbs.**

Hamilton's line of wash down casters and wheels are specially formulated for the harshest applications. Splash them with blood, brine, salt, grease, oils and chemicals.

### Industries & Applications:

- Food Manufacturing
- Pharmaceutical
- Research labs & Clean Rooms
- Marine & Fisheries
- Food service & Hospitality hoists



### Endurance Stainless

**Load Rating (ea.): Up to 750 lbs.**

- For sanitary or corrosive environments
- Small, compact design
- Forged Stainless, incredibly durable



### Workhorse Stainless

**Load Rating (ea.): Up to 1600 lbs.**

- Rugged hot forged swivel construction
- Wheel Diameters: 6" - 12"
- High lustre finish



### Champion Stainless

**Load Rating (ea.): Up to 3200 lbs.**

- Rugged hot forged swivel construction
- CNC machined raceways
- Wheel Diameters: 4" - 8"



### Stainless Light Duty

**Load Rating (ea.): 240 – 325 lbs.**

- Stamped double ball raceways
- Sealed swivel assembly standard
- Seven wheel choices



### Stainless Medium Duty

**Load Rating (ea.): 350 – 800 lbs.**

- Cold forged swivel construction
- High luster finish
- Wheel Diameters: 5" - 8"



### V-Groove Stainless

**Load Rating (ea.): Up to 1000 lbs.**

- Type 303 for corrosive environments
- Choose from Delrin or Stainless Steel Precision Ball Bearings
- Custom sizes available



### Stainless Steel

**Load Rating (ea.): 450 - 1500 lbs.**

- 303 Stainless Steel
- High corrosion resistance
- Best for heavy loads wash down



### Nylast®

**Load Rating (ea.): 2000 - 30,000**

- Heavy duty cast nylon
- Highest capacity in category
- Viable alternative to steel



### White Nylon

**Load Rating (ea.): 350 - 1100 lbs.**

- Molded Solid Nylon 6
- USFDA approved for food contact
- Wheel Diameters: 4" - 6"



### Aqualite®

**Load Rating (ea.): 200 - 900 lbs.**

- Low cost light duty solution
- USFDA approved for food contact
- Cleanable with steam or detergent



### Versa-Tech®

**Load Rating (ea.): 240 - 500 lbs.**

- Non-marking soft rubber
- Quiet and cushions load
- Soft 65A poly



### Poly-Tech®

**Load Rating (ea.): 350 - 1200 lbs.**

- Resilient wheels for sanitary use.
- Steam cleanable
- 95A poly tread



### Unilast

**Load Rating (ea.): 750 - 3200 lbs.**

- Standard hardness of 75-80 Shore D
- Solid elastomer design
- Well suited for hostile environments



### Stainless Steel V-Groove

**Load Rating (ea.): 350 - 1200 lbs.**

- Corrosive, sanitary, or high heat applications
- Runs on inverted angle iron
- Wheel Diameters: 4" - 8"



### Stainless Steel U-Groove

**Load Rating (ea.): 750 - 3200 lbs.**

- Corrosive, sanitary, or high heat applications
- Runs on tube or pipe track
- Wheel Diameters: 4" - 10"



Scan to learn how Hamilton's casters and wheels perform in wash down environments.

